



TECHNICAL DATA

Cycle times (*)	4 Wash Cycles 1. 3, 6, 9.5 & 12 mins (12mins = Thermal Disinfection)
Water consumption	3.5 to 17.5 l/cycle
Tank capacity	10,6 l
Tank heating	1,7 kW
Power supply	415 / 50 / 3N (240 / 50 / 1)
Booster loading	
Standard	6,2 kW
Alternative	2,1 kW
Total loading	
Standard	6.8 kW 3 x 15 A
Alternative	3.3 kW 20 A
Wash pump	0.5 kW kW
Rack size	500 x 500 500 x 530 mm
Loading height	425 mm
Noise level	57,7 dB (A)
Weight (gross / net)	70 / 60 kg

PRODUCT ADVANTAGES

- **VISIOTRONIC-TOUCH** control: colour touchscreen (displays text and graphic) in conjunction with single-button control and remaining cycle time indication
- **WASHSMART** app: controlling your warewash operation with smart technology: status and messages, usage and operating costs, hygiene, service and consumables order
- **2IN1** double rack system: two racks can be washed in a single wash cycle. One rack of cups can be washed underneath, while a second rack containing dishes and cutlery can also be washed above it. Thanks to the optimum use of the entire wash chamber the performance of the machine is doubled
- **4 WASH CYCLES** - TOP-DRY drying adds 03:00mins to each cycle.....
SHORT - 03:00mins
STANDARD - 06:00mins
LONG - 09:00mins
THERMAL DISINFECTION - 12:00mins - based on EN ISO 15883
- **CLIP-IN** wash and rinse arms: wash and rinse arms can be removed with one hand and without any tools
- Intelligent data documentation: automatic recording of important operational data and consumptions and indication on the display
- **USB-interface**: comfortable download of operational data in form of a protocol via USB - logbook compliant to DIN SPEC 10534
- **GENIUS-X²** fine filter system: advanced filter system with pre-wash function reduces detergent consumption up to 35 %
- Interlocked strainer: prevents operation without tank strainer
- Optional refill signal: monitors contents of external chemical containers
- Hygiene program: for removal of calcium carbonate and other deposits from wash chamber

CONNECTIONS

① Drain hose	2,000 mm ID20/ OD25
② Supply hose	2,000 mm R 3/4"
Required flow rate	5 l/min
Flow pressure	0.5 (0.8 with softener) - 10 bar
Max. supply water temperature	60 °C
③ Power cord	2.000 mm
Supply hose for	
④ Detergent	2.500 mm
⑤ Rinse aid	not in use mm

*Thermostop guarantees required temperatures with cold water connection, the actual cycle times extend accordingly.

DIMENSIONAL DRAWING

