

Automatic Rack Type Dishwasher, Capacity up to 240 racks, 4.320 plates or 8.640 glasses per hour.

**Product Advantages:**

- High-performance prewash zone L
- 100% hygiene - deep drawn stainless steel wash tank with stainless steel tank strainer system
- Full body, door & tank insulation included for lowest heat loss, best work environment & lower operating costs
- Heat recovery C20 - fills on hot water operates on cold water for reduced energy consumption
- Low 140L per hour triple rinse with rinse pump to guarantee rinse volume
- 3-speeds (120/180/240 racks/h)
- High performance DS drying module with integrated control panel
- Strainer Control PROOF
- Rinse actuator & autotimer
- Stainless steel wash pumps
- Protronic XL TFT touch screen control panel
- SENSOTRONIC - variable rinse water volume based on speed selected and items & volume to be washed
- Automatic self check during machine start up - BEST START
- 3kW pre wash stand-by heater providing best wash results
- Emergency stop switch on entry
- AUTOMATIC SOIL REMOVAL (ASR) - less manual handling, less dumping & re-filling, higher throughput
- Including AUTO-CLEAN
- Including RACK-FLOW Sensor system



1 fresh water connection, soft	R 3/4" 0 - 3°d, (0,5mmol/l); 140-190 l/h; demineralized water blended to have appr. 80 µs/cm
1.1 hot water connection for separate tank fill	R 3/4" 0 - 3°d; (1,4mmol/l)
2 drain	DN 50
3 power supply (depending on specific model and type of heating)	with standard model (incl. C20 / incl. dryer 4.5 kW) appr. 34.0 kW 57 Amp., 3 x 63 mm <sup>2</sup>
4 Ventilation / vent. condition (depending on specific model)	with standard model (incl. C20) appr. 280 m <sup>3</sup> /h, 27-29°C, 3,1 g/m <sup>3</sup> humidity
5 main switch	

