



TECHNICAL DATA

Cycle times*	4 Wash Cycles
	1. 60sec
	2. 90sec
	3. 180sec
	4. Continuous (max.20mins)
Water consumption	Upper level 2.0 l / rack. Lower level 2.5l / rack
Tank capacity	30 l
Tank heating	3 kW
Power supply	415 / 50 / 3N
Booster loading Standard	9.1 kW
Total loading Standard	13.5 3 x 25 A
Alternative	10.4 3 x 20 A
Wash pump	1.2 kW
Rack size	500 x 500 mm
Loading height	Upper Level 440 mm Lower Level 235mm
Noise level	70 dB (A)
Weight (gross / net)	160 / 140 kg

PRODUCT ADVANTAGES

- **Double capacity:** the TLW provides twice the capacity of a conventional hood-type dishwasher, thanks to an additional chamber, but with the same space requirement
- **Maximum flexibility:** simultaneous washing of different wash ware, such as porcelain dishes, cutlery or cooking utensils, in two separate wash chambers
- **Space saving wash organisation:** For heavily soiled wash ware, the TLW has a special utensil wash program. Due to the extended washing time, the pre-soaking effect is already integrated into the washing process, so that the wash ware no longer needs to be pre-soaked. This saves valuable space in the kitchen organisation
- **VISIOTRONIC -TOUCH control:** colour touchscreen (displays text and graphic) in conjunction with single button control with remaining time indication
- **WASHSMART app:** controlling your warewash operation with smart technology: status and messages, usage and operating costs, hygiene, service and consumables order
- **SENSO-ACTIVE resource management:** constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum in order to guarantee a fully hygienic wash result
- **Exhaust energy storage:** the fully enclosed 4-sided hood keeps steam and energy inside the system: energy saving up to 6 kW; less humidity in the kitchen area and better hygienic conditions
- **CLIP-IN wash and rinse arms:** wash and rinse arms can be removed with one hand and without any tools
- **Interlocked trainer:** prevents operation without tank strainer
- **EASY-CLEAN:** items with blue markings identify components which require cleaning
- **Thermolabel 71°C:** default temperature setting acc. European DIN can be switched by operator to a higher thermolabel setting
- **Watermark Approved - to WMTS-101:2018, Cert. WMKT21944**
- **NOT SUITABLE FOR CORNER INSTALLATIONS. STRAIGHT LINE / PASS THROUGH INSTALLATIONS ONLY**

* Thermostat guarantees required temperatures with cold water, the actual cycle times extend accordingly.

For corner operation we recommend to make the right side of the machine accessible for service.

For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or a HOBART HYDROLINE water treatment system.

CONNECTIONS

① Drain hose - 2nd drain required - see point 6 below	2,000 mm ID 20 / OD 25
Reverse Osmosis unit (RO-S)	Independent gravity waste to tundish
② Supply hose	2,000 mm R 3/4"
Required flow rate	5 l/min
Flow pressure	0.5 bar - 6 bar
Max. supply water temperature	60 °C 35 °C With ROS
③ Power cord	2,500 mm
Supply hose for	
④ Detergent	2,000 mm
⑤ Rinse aid	2,000 mm

DIMENSIONAL DRAWING

