



PRODUCT ADVANTAGES

- VISIOTRONIC control: single button control with remaining time indicator together with text and graphic display
- SENSO-ACTIVE resource management: constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum in order to guarantee a fully hygienic wash result
- POWER wash: high-pressure washing to wash heavily soiled wash items
- CLIP-IN wash and rinse arms: wash and rinse arms can be removed with one hand and without any tools
- USB-interface: download operational data via USB
- GENIUS-X² fine filter system: advanced filter system with pre-wash function reduces detergent consumption up to 35%
- ROTOR-X wash system: separate rotating upper and lower 4-spoke wash arms deliver dynamic wash power
- (Optional) Exhaust heat recovery & VAPOSTOP: prevents vapour to escape from machine when door is opened & uses steam to heat fresh feed water and reduces the amount of power needed, saving up to 5.2 kW
- Loading height: above-average loading height of 860 mm
- Intelligent energy management: the available energy is used continuously. Thus, at a low total loading value the heating time gets reduced
- Interlocked strainer: prevents operation without tank strainer
- EASY-CLEAN concept: blue markings in the machine help the operator to identify the components which require cleaning
- Hygiene programme: for removal of calcium carbonate and other deposits from wash chamber

TECHNICAL DATA

Cycle times*	120 / 240 / 360 sec. and special cycles
Water consumption	7.5 l/rack
Tank capacity	130 litres
Tank heating	6.1 kW
Power supply	415 / 50 / 3N
Booster loading	
Standard	15.3 kW
Alternative	9.1 kW
Total loading	
Standard	21.6 kW 3 x 35 A
Alternative	15.6 kW 3 x 35 A
Wash pump	2 x 2.9 kW 2 x 1,150 l/min
Rack size	1,240 x 700 mm
Loading height	860 mm
Noise level	70 dB (A)
Weight (gross / net)	315 / 295 kg

CONNECTIONS

① Drain hose	1,800 mm ID20 / OD25
② Supply hose	2,000 mm R 3/4" UXT - 2 x Hot connections
	UXT-ER - hot & cold connections
Required flow rate	5 l/min
Flow pressure	0.5 - 6 bar
Max. supply water temperature	60 °C
③ Power cord	2,000 mm
Supply hose for	
④ Detergent	2,500 mm
⑤ Rinse aid	2,500 mm

* Thermostop guarantees required temperatures with cold water connection, the actual cycle times extend accordingly.
For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or an external water softener of the product line HYDROLINE PROTECT.

DIMENSIONAL DRAWING

